



Anlin Panoramic

Style	Glazing Option	Air Argon	U-Factor	SHGC No-Grid	SHGC Grid	VLT	UV Block	Air Infiltration	CRF	STC Ratings		
										Standard 1/8 over 1/8	Sound Pack 3/16 over 1/8	Laminated 7/32 over 1/8
Single Slider	Infinite Plus	Air	.32	.23	.21	65%	95%	0.05	55	28	32	34
Single Hung	Infinite Plus	Air	.32	.23	.21	65%	95%	0.07	55	28	33	34
Picture Window	Infinite Plus	Air	.30	.24	.22	65%	95%	<.01	58	29	34	35
Single Slider	Infinite Plus	Argon	.27	.23	.21	65%	95%	0.05	59	28	32	34
Single Hung	Infinite Plus	Argon	.27	.23	.21	65%	95%	0.07	55	28	33	34
Picture Window	Infinite Plus	Argon	.25	.24	.22	65%	95%	<.01	57	29	34	35
Single Slider	Infinite Plus/QuadraTherm	Air	.27	.23	.21	63%	95%	0.05	44	28	32	34
Single Hung	Infinite Plus/QuadraTherm	Air	.26	.23	.21	63%	95%	0.07	43	28	33	34
Picture Window	Infinite Plus/QuadraTherm	Air	.25	.24	.21	63%	95%	<.01	45	29	34	35
Single Slider	Infinite Plus/QuadraTherm	Argon	.23	.22	.20	63%	95%	0.05	48	28	32	34
Single Hung	Infinite Plus/QuadraTherm	Argon	.23	.22	.20	63%	95%	0.07	47	28	33	34
Picture Window	Infinite Plus/QuadraTherm	Argon	.21	.23	.21	63%	95%	<.01	50	29	34	35
Single Slider	SunShield Plus	Air	.32	.16	.14	39%	98%	0.05	55	28	32	34
Single Hung	SunShield Plus	Air	.32	.16	.14	39%	98%	0.07	55	28	33	34
Picture Window	SunShield Plus	Air	.30	.16	.15	39%	98%	<.01	58	29	34	35
Single Slider	SunShield Plus	Argon	.28	.15	.14	39%	98%	0.05	59	28	32	34
Single Hung	SunShield Plus	Argon	.28	.15	.14	39%	98%	0.07	58	28	33	34
Picture Window	SunShield Plus	Argon	.26	.16	.14	39%	98%	<.01	62	29	34	35
Single Slider	SunShield Plus/QuadraTherm	Air	.27	.15	.14	38%	98%	0.05	44	28	32	34
Single Hung	SunShield Plus/QuadraTherm	Air	.27	.15	.14	38%	98%	0.07	43	28	33	34
Picture Window	SunShield Plus/QuadraTherm	Air	.25	.16	.14	38%	98%	<.01	45	29	34	35
Single Slider	SunShield Plus/QuadraTherm	Argon	.24	.15	.13	38%	98%	0.05	47	28	32	34
Single Hung	SunShield Plus/QuadraTherm	Argon	.24	.15	.13	38%	98%	0.07	47	28	33	34
Picture Window	SunShield Plus/QuadraTherm	Argon	.22	.15	.14	38%	98%	<.01	49	29	34	35

SHGC - Solar Heat Gain Coefficient

CRF - Condensation Resistance Factor

STC - Sound Transmission Class

VLT - Visible Light Transmittance (Note: VLT on NFRC label will vary as calculation is based on complete unit, not viewing area)



Anlin Panoramic

Style	Glazing Option	Air Argon	U-Factor	SHGC No-Grid	SHGC Grid	VLT	UV Block	Air Infiltration	CRF	STC Ratings		
										Standard 1/8 over 1/8	Sound Pack 3/16 over 1/8	Laminated 7/32 over 1/8
Single Slider	CoolShield Plus	Air	.32	.31	.28	70%	86%	0.05	55	28	32	34
Single Hung	CoolShield Plus	Air	.32	.31	.28	70%	86%	0.07	55	28	33	34
Picture Window	CoolShield Plus	Air	.30	.32	.29	70%	86%	<.01	58	29	34	35
Single Slider	CoolShield Plus	Argon	.28	.31	.28	70%	86%	0.05	59	28	32	34
Single Hung	CoolShield Plus	Argon	.28	.31	.28	70%	86%	0.07	58	28	33	34
Picture Window	CoolShield Plus	Argon	.26	.32	.29	70%	86%	<.01	61	29	34	35
Single Slider	CoolShield Plus/QuadraTherm	Air	.27	.30	.27	69%	86%	0.05	43	28	32	34
Single Hung	CoolShield Plus/QuadraTherm	Air	.27	.30	.27	69%	86%	0.07	43	28	33	34
Picture Window	CoolShield Plus/QuadraTherm	Air	.25	.31	.29	69%	86%	<.01	44	29	34	35
Single Slider	CoolShield Plus/QuadraTherm	Argon	.24	.30	.27	69%	86%	0.05	47	28	32	34
Single Hung	CoolShield Plus/QuadraTherm	Argon	.24	.30	.27	69%	86%	0.07	47	28	33	34
Picture Window	CoolShield Plus/QuadraTherm	Argon	.22	.31	.28	69%	86%	<.01	48	29	34	35
Single Slider	Luminance	Air	.33	.54	.48	79%	71%	0.05	54	28	32	34
Single Hung	Luminance	Air	.33	.54	.48	79%	71%	0.07	54	28	33	34
Picture Window	Luminance	Air	.31	.56	.50	79%	71%	<.01	57	29	34	35
Single Slider	Luminance	Argon	.29	.54	.48	79%	71%	0.05	58	28	32	34
Single Hung	Luminance	Argon	.29	.54	.48	79%	71%	0.07	57	28	33	34
Picture Window	Luminance	Argon	.27	.56	.50	79%	71%	<.01	60	29	34	35
Single Slider	Luminance/QuadraTherm	Air	.28	.51	.46	77%	73%	0.05	43	28	32	34
Single Hung	Luminance/QuadraTherm	Air	.27	.52	.46	77%	73%	0.07	42	28	33	34
Picture Window	Luminance/QuadraTherm	Air	.26	.54	.48	77%	73%	<.01	44	29	34	35
Single Slider	Luminance/QuadraTherm	Argon	.25	.52	.47	77%	73%	0.05	46	28	32	34
Single Hung	Luminance/QuadraTherm	Argon	.25	.52	.47	77%	73%	0.07	46	28	33	34
Picture Window	Luminance/QuadraTherm	Argon	.23	.54	.49	77%	73%	<.01	47	29	34	35

SHGC - Solar Heat Gain Coefficient

CRF - Condensation Resistance Factor

STC - Sound Transmission Class

VLT - Visible Light Transmittance (Note: VLT on NFRC label will vary as calculation is based on complete unit, not viewing area)



Anlin Panoramic

Structural Performance Data

Panoramic	Min Size	Max Size	Rating ⁽¹⁾
Single Hung (SH)	10 3/4 x 21	48 x 120 ⁽³⁾	LC30
Single Slider (XO,OX)	21 x 9	96 x 72	R20
	21 x 13 ⁽²⁾		
End Vent Slider (XOX)	42 x 9	144 x 72 ⁽⁵⁾	R20
	42 x 13 ⁽²⁾		

- (1) Rating based on Max Size unit
- (2) Minimum Size with True Action Lock and Sash Bolt Option
- (3) Maximum Single Hung vent height is 36"
- (4) PW over 96" wide must be tempered
- (5) End Vent Slider (XOX) configuration is 4/2/4

Combinations ⁽¹⁾	Min Size	Max Size	Rating
PW over XO, OX	21 x 24	96 x 96	R20
PW over XOX	42 x 24	96 x 96	R20
PW/PW	18 x 8 1/2	120 x 96	R15
PW/PW/PW	27 x 8 1/2	144 x 72	R15