

Anlin Panoramic Series

Style	Glazing Option	Air Argon	U-factor	SHGC No-Grid	SHGC Grid	VLT %			UV Block	Air Infil	CRF	STC Ratings		
						IG	NFRC NG	NFRC G				Standard 1/8 / 1/8	Sound Pack 3/16 / 1/8	Laminated 7/32 / 1/8
Single Slider	SunMatrix Plus	Air	.31	.19	.17	52	43	39	99%	0.04	56	29	34	35
Single Hung	SunMatrix Plus	Air	.31	.19	.17	52	43	38	99%	0.03	55	28	35	37
Picture Window	SunMatrix Plus	Air	.30	.20	.18	52	45	40	99%	<.01	59	29	34	35
Single Slider	SunMatrix Plus	Argon	.27	.18	.17	52	43	39	99%	0.04	59	29	34	35
Single Hung	SunMatrix Plus	Argon	.27	.18	.17	52	43	38	99%	0.03	58	28	35	37
Picture Window	SunMatrix Plus	Argon	.26	.19	.18	52	45	40	99%	<.01	63	29	34	35
Single Slider	SunMatrix Plus/QT	Air	.26	.18	.17	50	42	38	99%	0.04	44	29	34	35
Single Hung	SunMatrix Plus/QT	Air	.26	.18	.17	50	42	38	99%	0.03	43	28	35	37
Picture Window	SunMatrix Plus/QT	Air	.24	.19	.17	50	44	39	99%	<.01	46	29	34	35
Single Slider	SunMatrix Plus/QT	Argon	.23	.18	.16	50	42	38	99%	0.04	48	29	34	35
Single Hung	SunMatrix Plus/QT	Argon	.23	.18	.16	50	42	38	99%	0.03	47	28	35	37
Picture Window	SunMatrix Plus/QT	Argon	.22	.19	.17	50	44	39	99%	<.01	50	29	34	35
Single Slider	Infinite Plus	Air	.31	.23	.21	65	53	48	95%	0.05	56	29	34	35
Single Hung	Infinite Plus	Air	.31	.23	.21	65	53	48	95%	0.07	55	28	35	37
Picture Window	Infinite Plus	Air	.30	.24	.22	65	56	50	95%	<.01	59	29	34	35
Single Slider	Infinite Plus	Argon	.27	.23	.21	65	53	48	95%	0.05	59	29	34	35
Single Hung	Infinite Plus	Argon	.27	.23	.20	65	53	48	95%	0.07	58	28	35	37
Picture Window	Infinite Plus	Argon	.25	.24	.22	65	56	50	95%	<.01	63	29	34	35
Single Slider	Infinite Plus/QT	Air	.26	.22	.20	63	52	47	95%	0.05	44	29	34	35
Single Hung	Infinite Plus/QT	Air	.26	.22	.20	63	52	47	95%	0.07	43	28	35	37
Picture Window	Infinite Plus/QT	Air	.25	.24	.21	63	54	49	95%	<.01	46	29	34	35
Single Slider	Infinite Plus/QT	Argon	.23	.22	.20	63	52	47	95%	0.05	48	29	34	35
Single Hung	Infinite Plus/QT	Argon	.23	.22	.20	63	52	47	95%	0.07	47	28	35	37
Picture Window	Infinite Plus/QT	Argon	.21	.23	.21	63	54	49	95%	<.01	50	29	34	35

SHGC: Solar Heat Gain Coefficient
U-Factor: Insulating Value

IG VLT: Viewing Area, Visible Light Transmittance
NFRC VLT: Entire Unit, Visible Light Transmittance

AIR INFILTRATION: Amount of air which passes through the unit
STC RATING: Measurement of units ability to reduce sound

Anlin Panoramic Series

Style	Glazing Option	Air Argon	U-factor	SHGC No-Grid	SHGC Grid	VLT %			UV Block	Air Infil	CRF	STC Ratings		
						IG	NFRC NG	NFRC G				Standard 1/8 / 1/8	Sound Pack 3/16 / 1/8	Laminated 7/32 / 1/8
Single Slider	SunShield Plus	Air	.31	.16	.14	39	32	29	98%	0.04	56	29	34	35
Single Hung	SunShield Plus	Air	.31	.15	.14	39	32	29	98%	0.03	55	28	35	37
Picture Window	SunShield Plus	Air	.30	.16	.15	39	33	30	98%	<.01	59	29	34	35
Single Slider	SunShield Plus	Argon	.28	.15	.14	39	32	29	98%	0.04	59	29	34	35
Single Hung	SunShield Plus	Argon	.28	.15	.14	39	32	29	98%	0.03	58	28	35	37
Picture Window	SunShield Plus	Argon	.26	.16	.14	39	33	30	98%	<.01	63	29	34	35
Single Slider	SunShield Plus/QT	Air	.26	.15	.14	38	31	28	98%	0.04	44	29	34	35
Single Hung	SunShield Plus/QT	Air	.26	.15	.13	38	31	28	98%	0.03	43	28	35	37
Picture Window	SunShield Plus/QT	Air	.25	.16	.14	38	33	29	98%	<.01	45	29	34	35
Single Slider	SunShield Plus/QT	Argon	.24	.15	.13	38	31	28	98%	0.04	47	29	34	35
Single Hung	SunShield Plus/QT	Argon	.24	.14	.13	38	31	28	98%	0.03	47	28	35	37
Picture Window	SunShield Plus/QT	Argon	.22	.15	.14	38	33	29	98%	<.01	49	29	34	35
Single Slider	CoolShield Plus	Air	.32	.31	.28	70	58	52	86%	0.05	55	29	34	35
Single Hung	CoolShield Plus	Air	.32	.31	.28	70	58	51	86%	0.07	55	28	35	37
Picture Window	CoolShield Plus	Air	.30	.32	.29	70	60	54	86%	<.01	59	29	34	35
Single Slider	CoolShield Plus	Argon	.28	.31	.28	70	58	52	86%	0.05	59	29	34	35
Single Hung	CoolShield Plus	Argon	.28	.30	.27	70	58	51	86%	0.07	58	28	35	37
Picture Window	CoolShield Plus	Argon	.26	.32	.29	70	60	54	86%	<.01	62	29	34	35
Single Slider	CoolShield Plus/QT	Air	.26	.30	.27	69	56	50	86%	0.05	44	29	34	35
Single Hung	CoolShield Plus/QT	Air	.26	.30	.27	69	56	50	86%	0.07	43	28	35	37
Picture Window	CoolShield Plus/QT	Air	.25	.31	.29	69	59	53	86%	<.01	45	29	34	35
Single Slider	CoolShield Plus/QT	Argon	.24	.30	.27	69	56	50	86%	0.05	47	29	34	35
Single Hung	CoolShield Plus/QT	Argon	.24	.30	.27	69	56	50	86%	0.07	47	28	35	37
Picture Window	CoolShield Plus/QT	Argon	.22	.31	.28	69	59	53	86%	<.01	47	29	34	35

SHGC: Solar Heat Gain Coefficient
U-Factor: Insulating Value

IG VLT: Viewing Area, Visible Light Transmittance
NFRC VLT: Entire Unit, Visible Light Transmittance

AIR INFILTRATION: Amount of air which passes through the unit
STC RATING: Measurement of units ability to reduce sound

Anlin Panoramic Series

Style	Glazing Option	Air Argon	U-factor	SHGC No-Grid	SHGC Grid	VLT %	VLT%	VLT%	UV Block	Air Infil	CRF	STC Ratings		
						IG	NFRC NG	NFRC G				Standard 1/8 / 1/8	Sound Pack 3/16 / 1/8	Laminated 7/32 / 1/8
Single Slider	Luminance	Air	.33	.53	.48	79	65	58	71%	0.05	55	29	34	35
Single Hung	Luminance	Air	.33	.53	.48	79	65	58	71%	0.07	54	28	35	37
Picture Window	Luminance	Air	.31	.56	.50	79	68	61	71%	<.01	58	29	34	35
Single Slider	Luminance	Argon	.29	.53	.48	79	65	58	71%	0.05	58	29	34	35
Single Hung	Luminance	Argon	.29	.53	.48	79	65	58	71%	0.07	57	28	35	37
Picture Window	Luminance	Argon	.27	.56	.50	79	68	61	71%	<.01	62	29	34	35
Single Slider	Luminance/QT	Air	.27	.51	.46	77	64	57	73%	0.05	43	29	34	35
Single Hung	Luminance/QT	Air	.27	.51	.46	77	64	57	73%	0.07	42	28	35	37
Picture Window	Luminance/QT	Air	.26	.54	.48	77	67	60	73%	<.01	44	29	34	35
Single Slider	Luminance/QT	Argon	.25	.52	.46	77	64	57	73%	0.05	46	29	34	35
Single Hung	Luminance/QT	Argon	.24	.51	.46	77	64	57	73%	0.07	46	28	35	37
Picture Window	Luminance/QT	Argon	.23	.54	.49	77	67	60	73%	<.01	48	29	34	35

SHGC: Solar Heat Gain Coefficient
U-Factor: Insulating Value

IG VLT: Viewing Area, Visible Light Transmittance
NFRC VLT: Entire Unit, Visible Light Transmittance

AIR INFILTRATION: Amount of air which passes through the unit
STC RATING: Measurement of units ability to reduce sound



Anlin Panoramic

Structural Performance Data

Catalina - Maximum View/Egress	Min Size	Max Size	Rating ⁽¹⁾
Single Hung (SH)	10 3/4 x 21	48 x 120 ⁽³⁾	LC30
Single Slider (XO,OX)	21 x 9	96 x 72	R20
	21 x 13 ⁽²⁾		
End Vent Slider (XOX)	42 x 9	144 x 72 ⁽⁵⁾	R20
	42 x 13 ⁽²⁾		

- (1) Rating based on Max Size unit
- (2) Minimum Size with True Action Lock and Sash Bolt Option
- (3) Maximum Single Hung vent height is 36"
- (4) PW over 96" wide must be tempered
- (5) End Vent Slider (XOX) configuration is 4/2/4

Combinations	Min Size	Max Size	Rating
PW over XO, OX	21 x 24	96 x 96	R20
PW over XOX	42 x 24	96 x 96	R20
PW/PW	18 x 8 1/2	120 x 96	R15
PW/PW/PW	27 x 8 1/2	144 x 72	R15